

## Product Information PG.20.01

24-10-2021

### GP 80

#### Description

GP 80 is a modern gearbox oil. The product guarantees a significant reduction in friction and heat generation and this provides maximum power delivery to the rear wheel. GP 80 has been specifically developed for use on the circuit but can also be used very effectively in road bikes.

#### Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

#### Specifications

API GL-4

#### Typicals

|                                      |       |
|--------------------------------------|-------|
| Density at 15 °C, kg/l               | 0,884 |
| Viscosity 40 °C, mm <sup>2</sup> /s  | 77,00 |
| Viscosity 100 °C, mm <sup>2</sup> /s | 9,50  |
| Viscosity Index                      | 98    |
| Flash Point COC, °C                  | 205   |
| Pour Point, °C                       | -27   |
| Acid number, mgKOH/g                 | 1,10  |
| Sulphate Ash, %                      | 0,03  |
| Brookfield -26°C, mPa.s              | 62400 |

#### Available packagings



70172  
1 L bottle



74273  
20 L Bag in  
Box



70176  
60 L drum