

Product Information 01.20.40

27-04-2024

HDX 10W-40

Description

HDX 10W-40 is a motor oil based on premium solvent-refined base oils with additives to achieve the following properties:

- Very high resistance to wear, corrosion and foaming.
- A high and stable viscosity index

Application

HDX 10W-40 is a motor oil suitable for petrol engines in all seasons, along with diesel engines for cars and vans working under light conditions. Not suitable for turbo diesels that require a minimum of an API CD or Mil-L-2104 C/D level.

Specifications

API SF/CC

CCMC G2/D1

Typicals

Density at 15 °C, kg/l	0,867
Viscosity -25 °C, mPa.s	5270
Viscosity 40 °C, mm ² /s	93,80
Viscosity 100 °C, mm ² /s	14,20
Viscosity Index	154
Flash Point COC, °C	236
Pour Point, °C	-30
Total Base Number, mgKOH/g	3,5
Sulphate Ash, %	0,86

Available packagings



00203
1 L bottle



00303
5 L can



35033
20 L pail



10115
60 L drum



10215
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.