

Product Information PF.20.08

02-07-2022

HPX R 15

Description

HPX R 15W is an advanced fork oil. The product is formulated from special, highly refined, synthetic base oils. The addition of the most advanced additives makes HPX R 15W a high-tech product for use at Grand Prix level. HPX R 15W fork oil prevents corrosion, oxidation, leaking seals and foaming. It is especially suitable for Grand Prix motorcycles that have to perform in cross enduro, trail, Road and Off Road.

Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Typicals

Density at 15 °C, kg/l	0,890
Viscosity -20 °C, mPa.s	3670
Viscosity 20 °C, mm ² /s	168,00
Viscosity 40 °C, mm ² /s	62,70
Viscosity 100 °C, mm ² /s	10,70
Viscosity Index	161
Flash Point COC, °C	225
Pour Point, °C	-33

Available packagings



70216
1 L bottle



74281
20 L Bag in
Box



70218
60 L drum