

Product Information PG.20.03

02-12-2021

SP Gear Oil

Description

SP Gear Oil is a high-grade 'total drive line' transmission oil. The synthetic formula provides outstanding protection to and proper functioning of the transmission and clutch under all temperature conditions. The product has been specially developed for gearboxes, final drives and differentials on modern Road and Off Road motorcycles, scooters and quads. SP Gear Oil is suitable for both recreational and competition use.

Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Specifications

API GL-4/5

Typicals

| | |
|--------------------------------------|-------|
| Density at 15 °C, kg/l | 0,874 |
| Viscosity 40 °C, mm ² /s | 83,80 |
| Viscosity 100 °C, mm ² /s | 15,20 |
| Viscosity Index | 192 |
| Flash Point COC, °C | 182 |
| Pour Point, °C | -48 |
| Brookfield -40°C, mPa.s | 66600 |

Available packagings



70309
1 L bottle



74302
20 L Bag in
Box



74113
60 L drum