

## Product Information PM.40.13

26-04-2024

### Technomoto Scooter 4T 5W-40

#### Description

Scooter 4T 5W-40 is a synthetic 4-stroke scooter engine oil. The latest generation of additive technology ensures optimum engine wear protection, even for engines with a 'start/stop' system. Scooter 4T 5W-40 has been developed for optimum fuel economy with the latest generation of modern 4-stroke scooters and guarantees:

- Minimal oil consumption
- Excellent viscosity properties even at low temperatures, which significantly prevents wear on cold starts
- Excellent cleaning properties ensure long-term and optimum engine performance
- Excellent lubrication properties throughout the entire service life

#### Application

Putoline Oil is a Dutch manufacturer and supplier of high quality oils and lubricants for motorcycles, scooters and quads only. This is what makes us unique. Almost 50 years of experience and continual research allows Putoline to provide cutting edge products at the best price/quality ratio. Manufacturing our own products guarantees consistent high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

#### Specifications

JASO MB

API SN

ACEA A3/B4

#### Typicals

Density at 15 °C, kg/l	0,856
Viscosity -30 °C, mPa.s	5880
Viscosity 40 °C, mm <sup>2</sup> /s	92,20
Viscosity 100 °C, mm <sup>2</sup> /s	14,70
Viscosity Index	167
Flash Point COC, °C	228
Pour Point, °C	-42
Total Base Number, mgKOH/g	10,8
Sulphate Ash, %	1,32
Molybdenum, mg/kg	110

#### Available packagings



70424  
1 L bottle



74267  
20 L Bag in  
Box



70521  
60 L drum



70425  
200 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.