

Product Information PT.30.05

25-04-2024

TT Scooter +

Description

TT Scooter + is a high performance 2-stroke oil. Its high quality makes the product suitable for modern, replica race scooters. TT Scooter + is recommended for regular and high performance road use. It is suitable for pre-mix and injection systems. Recommended mix ratio: 2-4%.

Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Specifications

API TC+

JASO FD (Low Smoke)

ISO-L-EGD

Piaggio Hexagon

TISI

Typicals

Density at 15 °C, kg/l 0,875

Viscosity 40 °C, mm²/s 48,00

Viscosity 100 °C, mm²/s 8,90

Viscosity Index 168

Flash Point PM, °C 84

Pour Point, °C -45

Total Base Number, mgKOH/g 2,9

Sulphate Ash, % 0,12

Available packagings



70477
1 L bottle



74425
20 L Bag in
Box



70480
60 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.