

Product Information 01.20.30

17-05-2025

Subliem 15W-40

Description

Subliem 15W-40 is a modern, multifunctional motor oil based on premium solvent-refined base oils with state-of-the-art additives to achieve the following properties:

- Very powerful dispersion and detergency (thereby preventing a high build-up of black sludge)
- Very high resistance to oxidation
- Highly effective against wear
- Good resistance to corrosion and foaming
- A high and stable viscosity index
- A low tendency to evaporate
- No negative effects on catalytic converters

Application

Subliem 15W-40 is a modern, multifunctional motor oil for petrol, diesel and LPG engines in cars and vans, whether or not fitted with an exhaust gas turbine.

Specifications

ACEA A3/B4

API SL/CF

VW 501.01/505.00

Typicals

Density at 15 °C, kg/l	0,879
Viscosity -20 °C, mPa.s	2800
Viscosity 40 °C, mm ² /s	88,90
Viscosity 100 °C, mm ² /s	13,50
Viscosity Index	135
Flash Point COC, °C	230
Pour Point, °C	-27
Total Base Number, mgKOH/g	10,7
Sulphate Ash, %	1,31

Available packagings



34345
20 L pail



37881
20 L can



10126
60 L drum



10226
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.