

Product Information PM.40.22

02-12-2021

Ester Tech Syntec 4+ 10W-40

Description

Ester Tech 4+ 10W-40 is a fully synthetic, superior performance 4-stroke competition engine oil. High-grade base oils combined with the revolutionary Ester Tech additive system guarantee outstanding performance in the following areas, among others:

- A very powerful lubricating film, even under the most extreme operating conditions
- Maximum engine performance
- A very high and extremely stable viscosity index
- Optimal functioning of the wet clutch
- Accurate and smooth gear-changing
- Superior protection against wear
- Minimum oil consumption as a result of low volatility Ester Tech 4+ 10W-40 has been exclusively developed for modern, high-tech, high to very high performance race and road motorcycles.

Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Specifications

API SM

JASO MA2

Typicals

Density at 15 °C, kg/l	0,853
Viscosity -25 °C, mPa.s	3370
Viscosity 40 °C, mm ² /s	83,60
Viscosity 100 °C, mm ² /s	13,60
Viscosity Index	163
Flash Point COC, °C	236
Pour Point, °C	-33
Total Base Number, mgKOH/g	7,6
Noack, %	6,5

Available packagings

70624
1 L bottle70625
4 L can74245
20 L Bag in
Box70614
60 L drum70615
200 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.