

Product Information PT.30.14

02-07-2022

Classic Scooter X

Description

Classic Scooter X is a high-grade 2-stroke scooter oil. Its unique, synthetic formulation gives it the following properties:

- Provides complete protection for classic 2-stroke scooter engines with cast iron or aluminium Nikasil cylinders
- Provides exceptional oil film strength
- Minimises carbon deposits and fouling on the spark plug
- Extends the service life of the engine Classic Scooter X has been specially formulated for high-performance road and race use. It is suitable for Lambretta, Vespa and all classic and modern 2-stroke scooters, pre-mix or injector. Classic Scooter X contains a blue colourant which clearly shows its presence in the fuel. Mix ratio 2-4%

Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Specifications

API TC

JASO FD

Husqvarna

ISO-L-EGD

Piaggio Hexagon

Typicals

Colour	BLAUW
Density at 15 °C, kg/l	0,872
Viscosity 40 °C, mm ² /s	70,50
Viscosity 100 °C, mm ² /s	11,00
Viscosity Index	151
Flash Point PM, °C	78
Pour Point, °C	-45
Total Base Number, mgKOH/g	2,9
Sulphate Ash, %	0,18

Available packagings



70700

1 L bottle

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.