

## Product Information 01.20.50

01-05-2024

### Multifleet SHPD 15W-40

#### Description

Multifleet SHPD 15W-40 is a modern, universal motor oil based on premium solvent-refined base oils, supplemented with carefully balanced additives. Multifleet SHPD 15W-40 features the following properties:

- Excellent detergency, thereby preventing deposits in the hot zone of the engine
- Excellent dispersion, which acts to prevent the formation of sediment and sludge
- High resistance to wear, corrosion and foaming
- A high and stable viscosity index
- A low ash content

#### Application

Multifleet SHPD 15W-40 is a universal lubricant oil suitable for petrol and diesel engines both with and without turbochargers, under all operating conditions in all seasons. If extended oil change intervals (up to 30,000 km) are permitted by the engine manufacturers, this oil can also be used.

#### Specifications

ACEA E7

API CH-4/SJ

Cat ECF-1-a

Cummins CES 20076/20077

Deutz DQC III-10

MAN M 3275-1

MB 228.1

MTU Type 2

Volvo VDS-2

#### Typicals

Density at 15 °C, kg/l	0,883
Viscosity -20 °C, mPa.s	5960
Viscosity 40 °C, mm <sup>2</sup> /s	102,00
Viscosity 100 °C, mm <sup>2</sup> /s	14,30
Viscosity Index	140
Flash Point COC, °C	220
Pour Point, °C	-33
Total Base Number, mgKOH/g	11,1
Sulphate Ash, %	1,43

### Available packagings



00331  
5 L can



37500  
15 L Bag in  
Box



32716  
20 L Bag in  
Box



35035  
20 L pail



10059  
20 L can



10111  
60 L drum



33102  
200 L drum



10211  
208 L drum



10730  
1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.