

Product Information 02.10.10 17-05-2025

Gear Oil 80W-90

Description

Gearlube GL-1 80W-90 is a mineral lubricant oil for mechanical transmissions. This oil has a limited tendency to oxidation and foaming and protects the metal surface against corrosion.

Application

Gearlube GL-1 80W-90 is used in gearboxes, differentials, steering boxes and transmissions for which the manufacturer does not recommend 'Extreme Pressure' oils or rejects them.

Specifications

API GL-1

Typicals

Density at 15 °C, kg/l	0,885
Viscosity 40 °C, mm²/s	154,00
Viscosity 100 °C, mm²/s	15,00
Viscosity Index	97
Flash Point COC, °C	258
Pour Point, °C	-12
Acid number, mgKOH/g	1,10

Available packagings



33506 60 L drum

11101



37513 15 L Bag in 20 L pail Box

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.