

Product Information PW.30.03

04-07-2025

DOT 5.1 Brake Fluid

Description

DOT 5.1 Brake Fluid is a high-grade, synthetic brake fluid. The product exceeds the requirements of motorcycle manufacturers.

Instructions for use:

- Replace the brake fluid every two years to continue to guarantee correct functioning
- Only use DOT 5.1 Brake Fluid when specified. Please consult your instruction book for the correct specifications
- Can be mixed with synthetic DOT 3 and DOT 4

Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Specifications

FMVSS 116 DOT 5.1

ISO 4925 Class 7

JIS K2233

Typicals

Density at 15 °C, kg/l	1,067
Viscosity -20 °C, mm ² /s	103
Viscosity -40 °C, mm ² /s	700
Viscosity 20 °C, mm ² /s	12,70
Viscosity 40 °C, mm ² /s	6,82
Viscosity 100 °C, mm ² /s	2,20
Wet Boiling Point, °C	185

Available packagings



74043

500 ml bottle



74586

15 L Bag-in-
Box

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.