

Product Information PM.30.07

05-07-2025

Putoline S4 10W-40

Description

S4 10W-40 is a mineral 4-stroke engine oil. The product provides total protection under regular riding conditions. S4 10W-40 is especially suitable for modern motorcycles, scooters and ATVs.

Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Specifications

API SM

JASO MA2

Typicals

Viscosity -25 °C, mPa.s	5420
Viscosity 40 °C, mm ² /s	95,80
Viscosity 100 °C, mm ² /s	14,70
Viscosity Index	160
Flash Point COC, °C	228
Pour Point, °C	-39
Total Base Number, mgKOH/g	8,2
Sulphate Ash, %	0,85
HTHS, mPa.s	3,93
Noack, %	9,9

Available packagings



74098
1 L bottle



74099
4 L can



74649
15 L Bag-in-
Box



74191
60 L drum



74162
200 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.