

## Product Information PV.10.03

20-09-2019

### Racing Grease

#### Description

Racing Grease is a special, EP2, lithium complex grease. The product is of the highest quality and has excellent mechanical stability. Its fine structure will not allow oil separation. Racing Grease is water resistant and fully suited to race applications.

#### Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

#### Specifications

N.L.G.I. Class 2

DIN 51825, KP2N-30

#### Typicals

Density at 15 °C, kg/l	0,950
Penetration (worked), 0,1 mm	280
Dropping Point, °C	> 260
Temperature Limits, °C	-30 / +140
Base oil Viscosity, 40 °C, mm <sup>2</sup> /s	210,00
4-ball welding load, N	2800

#### Available packagings



74114  
100 g tube



73610  
600 g pot

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.