

Product Information PV.20.01

02-11-2024

Ceramic Grease

Description

Ceramic Grease is a particularly especially high-grade assembly paste and high temperature lubricant grease without metal particles. Its unique formulation gives it the following properties:

- Very high temperature range (peak temperature approx. 1500°C)
- High pressure resistance.
- Reduces friction in moving parts
- Effective protection against corrosion
- Excellent protection against electrolytic corrosion (metal to metal contact where the least precious metal is affected.) Ceramic Grease is particularly suitable for use in:
 - Assembling/dismantling:
 - ABS system components
 - Brake components
 - Lambda sensors
 - Exhaust components
 - (Bolt) connections
 - Connections of different metals (e.g. steel/aluminium)
 - Components exposed to very high temperatures

Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Specifications

NLGI Grade 2/3

DIN 51825, KP2,5N-30

Typicals

Density at 15 °C, kg/l 1,000

Available packagings



74115
100 g tube



73612
600 g pot

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.