

## Product Information PM.40.40

20-04-2024

### Genuine V-Twin Motorcycle Oil SAE 20W-50

#### Description

Genuine V-Twin Motorcycle Oil SAE 20W-50 is a fully synthetic oil. The latest generation of synthetic base oils combined with the unique additives technology provide the following properties:

- Unequaled performance
- Low friction values
- Excellent cold-start protection
- Minimum oil consumption
- Optimal clutch action The product is suitable for all V-Twin motorcycles with combined or separate lubrication for the engine, gearbox and primary chain case for which SAE 20W-50 engine oil is specified.

#### Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

#### Specifications

API SN

JASO MA2

#### Typicals

Density at 15 °C, kg/l 0,849

Viscosity -15 °C, mPa.s 1720

Viscosity 40 °C, mm<sup>2</sup>/s 153,00

Viscosity 100 °C, mm<sup>2</sup>/s 21,40

Viscosity Index 170

Flash Point COC, °C 240

Pour Point, °C -60

Total Base Number, mgKOH/g 7,7

Sulphate Ash, % 0,85

#### Available packagings



74110  
1 L tin



74255  
20 L Bag in  
Box



74118  
60 L drum



74120  
200 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.