

Product Information PC.10.20

17-05-2025

Putoline Ultracool 12

Description

Ultracool 12 is a high-grade, ready-to-use long life coolant with a frost protection down to -37 °C. The patented LOBRID PSi-OAT additive technology guarantees excellent and long-term corrosion protection and long-term stability. The product has been specially developed for cooling systems made from aluminium and copper or aluminium alloys. Ultracool 12 can also be used safely in conventional cast iron cooling systems.

The use of powerful corrosion inhibitors means Ultracool 12 is practically unaffected by ageing and can be used for the entire service life of the engine. Optimal results can only be achieved with a 100% filling.

Ultracool 12 is completely free of amines, nitrites, borates and 2-ethylhexanoic acid.

Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Typicals

Density at 15 °C, kg/l	1,072
pH - value	8,0

Available packagings



74130
1 L bottle



74673
4 L can



74576
15 L Bag in
Box



74132
60 L drum



74133
200 L drum