

## Product Information PC.10.20

22-01-2021

### Putoline Ultracool 12

#### Description

Ultracool 12 is a high-grade, ready-to-use long life coolant (frost protection down to -40°C) for which a patented, silicate-free technology based upon carboxyl acids has been used.

The product has been specially developed for cooling systems made from aluminium and copper or aluminium alloys. Ultracool 12 can also be used safely in conventional cast iron cooling systems.

The use of powerful corrosion inhibitors means Ultracool 12 is practically unaffected by ageing and can be used for the entire service life of the engine. Optimal results can only be achieved with a 100% filling.

#### Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

#### Specifications

ASTM D3306/D4985/D6210

#### Typicals

Density at 15 °C, kg/l	1,045
pH - value	8,5
Crystallizationpoint, °C	-38

#### Available packagings



74130  
1 L bottle



74289  
20 L Bag in  
Box



74132  
60 L drum



74133  
200 L drum