

## Product Information 02.10.31

27-04-2024

### Gearlube GL-5 85W-140

#### Description

Gearlube GL-5 85W-140 is a mineral lubricant oil for mechanical transmissions, based on premium solvent-refined base oils, supplemented with special 'Extreme Pressure' additives, to achieve the following properties:

- Outstanding resistance to oxidation
- Very high resistance to rust, corrosion and foaming
- A low pour point
- Excellent 'Extreme Pressure' properties

#### Application

Gearlube GL-5 85W-140 is used under the most heavy-duty hypoid transmissions in rear axles, gearboxes and in all transmissions in which 'Extreme Pressure' oil is required.

#### Specifications

API GL-5

MIL-L-2105D

ZF TE-ML 07A/21A

#### Typicals

Density at 15 °C, kg/l	0,909
Viscosity 40 °C, mm <sup>2</sup> /s	340,00
Viscosity 100 °C, mm <sup>2</sup> /s	27,00
Viscosity Index	106
Flash Point COC, °C	245
Pour Point, °C	-15
Acid number, mgKOH/g	1,80

#### Available packagings



01329  
5 L can



36083  
20 L pail



31026  
20 L can



11107  
60 L drum



11207  
208 L drum



34505  
1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.