

## Product Information 02.30.10

26-04-2024

### ATF - A

#### Description

ATF - A is a premium, automatic transmission oil based on solvent-refined base oils. It is supplemented with additives to achieve the following properties:

- A very high and stable viscosity index
- A very low pour point
- Excellent oxidation stability
- Effective resistance to corrosion and foaming

#### Application

ATF - A can be used for automatic and semi-automatic gearboxes, power steering systems and other applications for which a type ATF - A oil is recommended.

#### Specifications

GM Type A Suffix A

ATF Type A Suffix A (TASA), ATF Dexron B

GM Dexron B

Allison C3

DTFR 13C120

Ford M2C41-A/B

MB 236.2

#### Typicals

Density at 15 °C, kg/l	0,857
Viscosity 40 °C, mm <sup>2</sup> /s	39,00
Viscosity 100 °C, mm <sup>2</sup> /s	7,22
Viscosity Index	151
Flash Point COC, °C	224
Pour Point, °C	-42
Total Base Number, mgKOH/g	0,8
Sulphate Ash, %	0,18

#### Available packagings



31265  
1 L bottle



36084  
20 L pail



11162  
60 L drum



34363  
200 L drum



11262  
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.