

Product Information VM.10.04

30-01-2023

VatOil Syntruck Plus 5W-30

Description

SynTruck Plus 5W-30 is a modern, fuel economy, synthetic diesel engine oil. It is based on the latest additive technology combined with very special base oils. The product is developed (considering the official instructions) to allow extended oil change intervals of 80.000km to 120.000km. SynTruck Plus 5W-30 properties:

- Powerful detergency
- Very strong dispersion
- Powerful resistance against wear
- Powerful resistance against corrosion and foam
- Prevents 'bore-polishing'

Application

SynTruck Plus 5W-30 is suitable for Heavy Duty diesel engines in trucks buses and industrial applications: vehicles operating under the toughest conditions all year round. SynTruck Plus 5W-30 is very suitable for EURO 3 and EURO 4 diesel engines in combination with diesel fuel with a low sulphur content. Always check the product recommendation database for the right application.

Specifications

ACEA E4, E7

API CI-4

MAN M 3377 / M 3277

Cat ECF-2

Cummins 20076/20078

DAF HP1/HP2

Deutz DQC IV-10

Mack EO-N, EO-M Plus

MB 228.5

MTU Type 3

Renault VI RLD-2, RXD

Scania LDF

Volvo VDS-3

Global DHD-1, JASO DH-1

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,855
Viscosity -30 °C, mPa.s	6420
Viscosity 40 °C, mm ² /s	71,6
Viscosity 100 °C, mm ² /s	12,10
Viscosity Index	168
Flash Point COC, °C	224
Pour Point, °C	-45
Total Base Number, mgKOH/g	12,2
Acid number, mgKOH/g	2,55
Sulphate Ash, %	1,35

Available packagings50007
20 L can50008
60 L drum50009
210 L drum