

Product Information VM.10.06

30-01-2023

SynTruck 10W-40

Description

SynTruck 10W-40 is a modern, fuel economic engine oil. It is produced with high quality, solvent refined, synthetic base oils and a well-balanced choice of additives. Developed (considering the official instructions) to allow extended oil change intervals for trucks.

Properties:

- Excellent detergency
- Very good dispersion
- Lower fuel consumption
- Powerful resistance against corrosion and foam

Application

SynTruck 10W-40 is suitable for petrol and Heavy Duty diesel engines with or without turbo-charging. The universal product is recommended for mixed fleets operating under all conditions all year round. SynTruck 10W-40 is suitable for application in EURO 4 and EURO 5 engines. Always check the product recommendation database for the right application.

Specifications

ACEA A3/B4, E7

API CI-4/SL

Cat ECF-1-a/ECF-2

Cummins CES 20077/20078

Detroit Diesel 93K215

Deutz DQC III-18

Global DHD-1

JASO DH-1

Mack EO-N

MAN M 3275

MB 228.3

MTU Type 2

Renault VI RLD-2

Volvo VDS-3

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,868
Viscosity -25 °C, mPa.s	4910
Viscosity 40 °C, mm ² /s	87,7
Viscosity 100 °C, mm ² /s	13,70
Viscosity Index	159
Flash Point COC, °C	222
Pour Point, °C	-36
Total Base Number, mgKOH/g	11,1
Sulphate Ash, %	1,43

Available packagings50050
20 L can50052
60 L drum50053
210 L drum