

## Product Information VG.10.03

30-01-2023

### VatOil Syntrag GL-4/5 75W-90

#### Description

SynTrag GL-4/5 75W-90 is a high performance, synthetic enriched gear oil. It is specially formulated to provide protection against wear and corrosion. The SynTrag GL-4/5 75W-90 properties:

- Excellent resistance against corrosion
- Smooth lubrication under hot and very cold temperature conditions
- Enhanced lubrication
- Day-to-day driving in summer and winter
- Sound absorbing properties
- Lower fuel consumption
- Easy shifting over a wide temperature range

#### Application

SynTrag GL-4/5 75W-90 is suitable for use in modern transmissions, axles and transaxles where the manufacturer specifies an API GL-4/5 type of lubricant. Always check the product recommendation database for the right application.

#### Specifications

API GL-4/5

MIL-L-2105

VW 501.50

#### Typicals

Density at 15 °C, kg/l	0,874
Viscosity 40 °C, mm <sup>2</sup> /s	83,8
Viscosity 100 °C, mm <sup>2</sup> /s	15,20
Viscosity Index	192
Flash Point COC, °C	182
Pour Point, °C	-48

#### Available packagings



50095  
1 L bottle



50096  
20 L can



50163  
60 L drum



50164  
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.