

Product Information 08.60.14

25-04-2024

Carsinus SS 68

Description

Carsinus SS 68 is a premium adhesion oil, based on specially selected, solvent-refined base oils with a naturally high viscosity index, supplemented with adhesion additives to achieve the following properties:

- Good adhesion properties
- Outstanding wear resistance
- Excellent rust and corrosion protection
- Excellent oxidation stability
- Excellent demulsifier
- Excellent air-release and resistance to foaming
- Does not affect synthetic seals
- A low pour point

Application

Carsinus SS 68 is suitable for general mechanical lubrication that requires non-drip oil. Carsinus SS 68 is also suitable for the lubrication of vertical guide-tracks and gear transmissions subjected to a light load.

Typicals

Density at 15 °C, kg/l	0,887
Viscosity 40 °C, mm ² /s	70,60
Viscosity 100 °C, mm ² /s	9,49
Viscosity Index	113
Flash Point COC, °C	215
Pour Point, °C	-24

Available packagings



57002
20 L pail



12115
60 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.