

Product Information VG.10.07

18-06-2024

VatOil Hypoid GL-5 85W-140

Description

Hypoid GL-5 85W-140 is a mineral lubricating oil. High quality solvent refined base oils and special 'Extreme Pressure' additives give the product the following properties:

- Excellent resistance against oxidation
- Very high resistance against wear, corrosion and foam
- Low pouring point
- Very good 'Extreme Pressure' properties

Application

Hypoid GL-5 85W-140 is used in hypoid differentials under very heavy duty conditions and should be used in all transmissions that require EP-transmission oils.

Specifications

API GL-5

MIL-L-2105D

ZF TE-ML 07A/21A

Typicals

Density at 15 °C, kg/l	0,909
Viscosity 40 °C, mm ² /s	340,00
Viscosity 100 °C, mm ² /s	27,00
Viscosity Index	106
Flash Point COC, °C	245
Pour Point, °C	-15
Acid number, mgKOH/g	1,80

Available packagings



50173
1 L bottle



50174
20 L can



50176
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.