

Product Information VM.30.03

30-01-2023

VatOil STOU 10W-30

Description

STOU 10W-30 is an up-to-date multifunctional STOU (Super Tractor Oil Universal). It is formulated with top-grade solvent refined base oils and additives to achieve the following properties:

- Powerful dispersion and detergency
- High resistance against wear, corrosion and foam
- Very strong resistance to oxidation
- Excellent 'Extreme Pressure' properties
- High and stable viscosity index

Application

STOU 10W-30 has been specially developed for everyday operating conditions in agriculture. The universal, multifunctional oil is what is known as an STOU: Super Tractor Oil Universal. It is therefore suitable for use as an all-purpose lubricant for: Petrol engines, Diesel engines and turbo diesels, Transmissions, also for wet brakes and Hydraulic systems.

Specifications

API SF/CG-4/GL-4

ACEA E3, MIL-L-2104D

Allison C4

Cat TO-2

Ford M2C159-C / M2C134-D

John Deere J27 / J20C

Massey Ferguson CMS M1145 / M1144 / M1139

Massey Ferguson CMS M1143 / M1135

MB 227.1

NH 410B

ZF TE-ML 06B / 07B

Typicals

Density at 15 °C, kg/l	0,876
Viscosity -25 °C, mPa.s	4730
Viscosity 40 °C, mm ² /s	70,6
Viscosity 100 °C, mm ² /s	11,40
Viscosity Index	154
Flash Point COC, °C	228
Pour Point, °C	-33
Total Base Number, mgKOH/g	11,3
Sulphate Ash, %	1,57

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings50184
20 L can50185
60 L drum50186
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.