

## Product Information VM.20.13

05-12-2021

### VatOil SynTech Diesel 10W-40

#### Description

SynTech Diesel 10W-40 is a semi-synthetic engine oil. The product helps to maintain high performances by providing protection under severe working conditions. Properties:

- Reduces formation of sludge and varnish deposits
- Low oil consumption
- Good cold start properties
- Outstanding wear protection
- Improved oil film strength

#### Application

SynTech Diesel 10W-40 is suitable for diesel engines of cars and vans. The product helps to maintain high performances under severe working conditions. Always check the product recommendation database for the right application.

#### Specifications

API SL/CF

ACEA A3/B4

MB 229.1

VW 501.01/505.00

#### Typicals

Density at 15 °C, kg/l	0,865
Viscosity -25 °C, mPa.s	5530
Viscosity 40 °C, mm <sup>2</sup> /s	90,50
Viscosity 100 °C, mm <sup>2</sup> /s	13,70
Viscosity Index	154
Flash Point COC, °C	226
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,0
Sulphate Ash, %	1,31
Noack, %	9,9

#### Available packagings



50231  
1 L bottle



50233  
20 L can



50234  
60 L drum



50235  
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.