

Product Information VM.40.02

30-01-2023

VatOil Scooter 4T 10W-40

Description

Scooter 4T 10W-40 is a semi-synthetic 4-stroke engine oil. It is produced with high quality solvent refined and synthetic base oils and additives to obtain the following properties:

- Reduces sludge on cylinder walls
- High and stable viscosity index
- Fast cold start
- Natural resistance against oxidation
- Minimal loss of friction and thus little wear
- Very low evaporation losses

Application

Scooter 4T 10W-40 is suitable for modern 4-stroke scooters. It prevents sliding, sticking and/or rough changing of the clutch-plates. Scooter 4T 10W-40 is developed and tested in cooperation with the most important motorcycle producers and has its performance demonstrated in the field. Always check the product recommendation database for the right application.

Specifications

API SG

JASO MA

Typicals

Density at 15 °C, kg/l	0,868
Viscosity -25 °C, mPa.s	3200
Viscosity 40 °C, mm ² /s	85,6
Viscosity 100 °C, mm ² /s	14,00
Viscosity Index	168
Flash Point COC, °C	218
Pour Point, °C	-33
Total Base Number, mgKOH/g	7,7
Sulphate Ash, %	0,94

Available packagings



50241
1 L bottle



50294
20 L can



50246
60 L drum



50295
200 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.