

Product Information 08.60.02

17-05-2025

Carsinus U 220

Description

Carsinus U 220 is a universal lubricant for machine tools, based on mineral oil. It is supplemented with additives to achieve the following properties:

- Resistant to high pressures and loads
- Very strong adhesion to metals
- Very strong 'anti stick-slip' ability
- Very effective resistance to wear, corrosion and foaming

Application

Carsinus U 220 can be used as a combined lubricant for slideways (stick-slip) in machine tools, as well as the associated hydraulic systems and gear transmissions.

Specifications

FZG 12

Typicals

Density at 15 °C, kg/l	0,895
Viscosity 40 °C, mm ² /s	220,00
Viscosity 100 °C, mm ² /s	18,20
Viscosity Index	95
Flash Point COC, °C	245
Pour Point, °C	-15

Available packagings



37089
20 L pail



35420
20 L can



12162
60 L drum



12259
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.