



Product Information 01.30.50

21-09-2021

Armado Synth 10W-40

Description

Armado Synth 10W-40 is a modern, synthetic diesel motor oil for commercial vehicles. With a combination of synthetic base oils and the latest additives technology, it is a product of unprecedented quality. Armado Synth 10W-40 redefines the standard for commercial vehicle motor oils. It features the following properties:

- Saves fuel and keeps oil consumption exceptionally low
- Ensures a smooth cold start, even at extremely low temperatures
- Ensures technical reliability and provides a strong lubricating film, even under the most extreme operating conditions - Exceptional cleaning ability
- Effectively prevents engine wear
- Copes exceptionally well with the long oil change intervals of today, for extra security
- Also prevents bore polishing
- Helps save costs

Application

Armado Synth 10W-40 is suitable for diesel engines operating under extreme conditions. The product is highly suitable for use in EURO 1,2,3,4 and 5 diesel engines with low exhaust gas emissions, in combination with diesel fuels with a very low sulfur content. Armado Synth 10W-40 has been developed, taking the manufacturers' instructions into account, to allow very long oil change intervals (100,000+ km) while retaining a very long service life that is free of problems.

Specifications

ACEA E4, E7

API CI-4

MAN M 3377/M 3277

MB 228.5

Volvo VDS-3

Renault VI RLD-2

Mack EO-N

Renault VI RXD

MTU Type 3

Deutz IV-10

Mack EO-M Plus

Cummins CES 20078

Global DHD-1

Detroit Diesel 93K215

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,862
Viscosity -25 °C, mPa.s	6350
Viscosity 40 °C, mm ² /s	95,90
Viscosity 100 °C, mm ² /s	14,00
Viscosity Index	148
Flash Point COC, °C	226
Pour Point, °C	-36
Total Base Number, mgKOH/g	12,6
Sulphate Ash, %	1,47
Noack, %	10,4

Available packagings



36729
20 L Bag in
Box



32040
20 L can



12171
60 L drum



12267
208 L drum



12311
Bulk