

## Product Information 01.40.09

27-07-2024

### Kroon-Oil Helar 0W-40

#### Description

Helar 0W-40 is a totally modern, synthetic, premium-class motor oil. Its very low viscosity, combined with advanced additives enables Helar 0W-40 to set a new standard in the motor oil sector, thanks to the following unique properties:

- Fuel savings of up to 4% and extremely low oil consumption: cost-effective and less chance of the oil level being too low
- A smooth cold start
- A powerful lubricating film, even in the most extreme operating conditions: high level of technical reliability
- Exceptional cleaning ability and compatible with catalytic converters: helps keep exhaust gas emissions low
- Effectively prevents engine wear: extremely long service life of moving parts
- Copes exceptionally well with the long oil change intervals of today: for added security

#### Application

Helar 0W-40 is a universal, synthetic motor oil, suitable for all (turbocharged) petrol and (turbocharged) diesel engines (both directly and indirectly injected). Helar 0W-40 can be used in cars and vans that require the specifications set out in the product sheet.

#### Specifications

ACEA A3/B4

API SN/CF

BMW Longlife-01

Ford WSS-M2C937-A

MB 229.3 / 229.5

Porsche A40

Renault RN0700/RN0710

VW 502.00/505.00

#### Typicals

Density at 15 °C, kg/l 0,845

Viscosity -35 °C, mPa.s 5900

Viscosity 40 °C, mm<sup>2</sup>/s 76,90

Viscosity 100 °C, mm<sup>2</sup>/s 13,40

Viscosity Index 180

Flash Point COC, °C 226

Pour Point, °C -48

Total Base Number, mgKOH/g 10,3

Sulphate Ash, % 1,09

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

### Available packagings



02226  
1 L bottle



35136  
4 L can



02343  
5 L can



37474  
15 L Bag in  
Box



36487  
20 L Bag in  
Box



57019  
20 L pail



12176  
60 L drum



12272  
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.