

# Product Information 02.10.33 15-07-2025

# Gearlube LS 80W-90

## Description

Gearlube LS 80W-90 is a mineral lubricant oil for mechanical transmissions, based on premium solvent-refined base oils, supplemented with special 'Extreme Pressure' additives, to achieve the following properties:

- Outstanding resistance to oxidation
- Very high resistance to rust, corrosion and foaming
- A low pour point
- Excellent 'Extreme Pressure' properties
- Outstanding 'Limited Slip' properties

### Application

Gearlube LS 80W-90 has been specially developed for the flawless lubrication of the so-called 'Limited Slip' and self-locking hypoid drives.

### Specifications

API GL-5 Limited Slip
MIL-L-2105D
Volvo 97321 (STD 1273,21)
ZF TE-ML 05C, 05N, 21N
P >1900 mg/kg (Liebherr)

## Typicals

Density at 15 °C, kg/l	0,877
Viscosity 40 °C, mm²/s	120,00
Viscosity 100 °C, mm²/s	15,00
Viscosity Index	125
Flash Point COC, °C	214
Pour Point, °C	-36
Total Base Number, mgKOH/g	2,0
Acid number, mgKOH/g	1,27
Brookfield -26°C, mPa.s	40700
Calcium, mg/kg	240
Zinc, mg/kg	0

### Available packagings

						1941 75	
01214	34617	37520	35076	11133	32494	11233	32648
1 L bottle	5 L can	15 L Bag-in-	20 L can	60 L drum	200 L drum	208 L drum	1000 L IBC
		Box					

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.