

## Product Information 09.40.05

17-05-2025

### Kroon-Oil Drauliquid Racing

#### Description

Drauliquid Racing is a very high quality, synthetic brake fluid. The product has been specifically developed for the range of tasks involved in the world of motorsport and motorcycle racing. The brake fluid has extremely high boiling points that provide a relatively high safety margin. Top quality glycol ether and ester base oils combined with a very advanced additives system provide Drauliquid Racing with the following properties:

- Very low viscosity, which means a very fast response time
- Extremely high boiling points, both wet and dry, for a wider safety margin
- Does not affect seals
- Provides outstanding protection against corrosion
- Can be mixed with all DOT 4 and DOT 5.1 brake fluids

#### Application

Drauliquid Racing is a superior brake fluid, specially developed for motorsport. The product is also particularly suitable for use in advanced braking systems in high to very high-powered sports cars. Drauliquid Racing can easily be mixed with other DOT 4 and DOT 5.1 brake fluids.

#### Specifications

FMVSS 116 DOT 4

SAE J1703/J1704

#### Typicals

Density at 15 °C, kg/l	1,081
Viscosity -40 °C, mm <sup>2</sup> /s	1520
Viscosity 100 °C, mm <sup>2</sup> /s	2,59
Boiling Point (reflux) , °C	328
Wet Boiling Point, °C	204
pH - value	7,1

#### Available packagings



35665

500 ml bottle



34489

20 L pail



37992

20 L can

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.