

Product Information 01.10.24 18-04-2024

HDX 50

Description

HDX 50 is a single-grade motor oil based on premium solvent-refined base oils with additives to achieve the following properties:

- Powerful detergency and dispersion
- High resistance to oxidation
- High resistance to wear, corrosion and foaming

Application

HDX 50 is a lubricant oil suitable for petrol engines as well as diesel engines for cars and vans working under light conditions. Not suitable for turbo diesels that require a minimum of API CD or Mil-L-2104 C/D level.

Specifications

API SF/CC
CCMC G2/D1
MIL-L-46152B/C
Ford M2C153-C (SF/CC)
Ford M2C9011-A
GM 6085M

Typicals

Density at 15 °C, kg/l	0,899
Viscosity 40 °C, mm²/s	240,00
Viscosity 100 °C, mm²/s	18,80
Viscosity Index	96
Flash Point COC, °C	258
Pour Point, °C	-12
Total Base Number, mgKOH/g	3,5
Acid number, mgKOH/g	2,25
Sulphate Ash, %	0,55

Available packagings



35056

20 L pail

20051





The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.