

Product Information 06.20.80

08-05-2024

Kroon-Oil TefTec AS

Description

TefTec AS is a technologically advanced lubricant. It contains a high concentration of PTFE, making it suitable for regular use in all weather conditions. TefTec AS reduces friction and is moisture and dirt-repellent. It also provides excellent adhesion, good lubrication and protection of the bicycle components.

Application

TefTec AS is suitable for derailleur systems, chains, shifters, cables and other moving parts. Thoroughly clean any parts to be lubricated first using Kroon-Oil BioSol XT. Then apply TefTec AS and remove any surplus product with a lint-free cloth. Regular re-application prevents excessive wear. Shake well before use! Vanilla scented.

With a useful turn-and-dose cap for clean and controlled application. Turn the cap one quarter turn and squeeze a drop from the bottle.

Typicals

Density at 15 °C, kg/l	0,879
------------------------	-------

Available packagings



22002

100 ml bottle

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.