

## Product Information 08.10.13

11-04-2024

### Perlus Bio

#### Description

Perlus Bio is a premium, biodegradable hydraulic oil based on plant oils supplemented with selected additives to achieve the following properties:

- A high and stable viscosity index
- Outstanding wear resistance
- Excellent resistance to rust and corrosion
- Excellent oxidation stability
- Does not affect synthetic seals
- A low pour point
- A low tendency to foam
- Rapid air-release

#### Application

Perlus Bio is ideally suited to all heavy-duty hydraulic systems that are required to operate at high pressures and within a wide temperature range. This hydraulic oil has been specially developed especially for situations in which environmental pollution can be expected, e.g. hose breakage and/or leakage.

#### Specifications

ISO 15380 HETG

CEC L-33-T-82 > 90% (3 weeks)

#### Typicals

Density at 15 °C, kg/l	0,919
Viscosity 40 °C, mm <sup>2</sup> /s	36,00
Viscosity 100 °C, mm <sup>2</sup> /s	8,11
Viscosity Index	211
Flash Point COC, °C	302
Pour Point, °C	-24
Acid number, mgKOH/g	0,40
Sulphate Ash, %	0,06

#### Available packagings



37077  
20 L pail



32031  
20 L can



12130  
60 L drum



12228  
208 L drum



32509  
1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.