

## Product Information 08.20.01

15-07-2025

### Compressol H 68

#### Description

Compressol H 68 is a compressor oil based on very highly refined base oils with a naturally high resistance to ageing. By adding highly effective additives the following properties are achieved:

- A low tendency to form carbon deposits
- Good oxidation stability
- Good corrosion protection
- Good wear resistance
- Low volatility

#### Application

Compressol H 68 is recommended for lubricating reciprocating compressors and for the drip feed lubrication of rotary vane compressors. High compression operating temperatures can occur in both these compressors. The high quality of the oil means that longer oil change intervals may be applied.

#### Specifications

DIN 51506 VDL

DIN 51352-2

#### Typicals

Density at 15 °C, kg/l	0,876
Viscosity 40 °C, mm <sup>2</sup> /s	68,00
Viscosity 100 °C, mm <sup>2</sup> /s	8,77
Viscosity Index	101
Flash Point COC, °C	236
Pour Point, °C	-33
Acid number, mgKOH/g	0,45

#### Available packagings



02218  
1 L bottle



02320  
5 L can



37767  
15 L Bag-in-  
Box



37973  
20 L can



12143  
60 L drum



34311  
200 L drum



12241  
208 L drum



35428  
1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.