

## Product Information 08.20.07

15-07-2025

### Compressol SCO 46

#### Description

Compressol SCO 46 is a screw compressor oil, formulated from special, premium mineral base oils. It is supplemented with special additives to achieve the following properties:

- Excellent oxidation stability
- Highly effective against wear
- Effective resistance to corrosion
- Powerful cleaning and stain-removing ability
- Good resistance to foaming
- Rapid separation of oil from condensation, thereby reducing the consumption of carbon cartridges in the oil-water separator.

#### Application

Compressol SCO 46 has been specially developed for the lubrication of oil-injected screw and rotary vane compressors with relatively high operating temperatures. The product contains a formula for effective water repellence. This allows you to comply with the current requirements relating to condensation drain in a responsible manner.

#### Specifications

ISO 6743-3A-DAH

#### Typicals

Density at 15 °C, kg/l	0,863
Viscosity 40 °C, mm <sup>2</sup> /s	46,00
Viscosity 100 °C, mm <sup>2</sup> /s	7,27
Viscosity Index	110
Flash Point COC, °C	212
Pour Point, °C	-33

#### Available packagings



33551  
5 L can



37766  
15 L Bag-in-  
Box



37971  
20 L can



12148  
60 L drum



12246  
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.