

Product Information 02.20.40

29-04-2024

Kroon-Oil Syngear MT/LD 75W-80

Description

Syngear MT/LD 75W-80 is a fuel-saving, low-viscosity synthetic Long Life transmission oil. It is supplemented with state-of-the-art additives to achieve the following properties:

- Outstanding thermal stability, maintaining the low viscosity for a long time
- Very high resistance to rust, corrosion and foaming
- A low pour point, which ensures easy gear-changing at very low temperatures
- Premium 'Extreme Pressure' properties
- Long usability

Application

Syngear MT/LD 75W-80 has been specially developed for modern, heavy-duty (compact) and manual transmissions in which operating temperatures can reach very high levels. This product is also particularly suitable for when the manufacturers require long oil change intervals. Consult the product specifications in the product sheet for correct usage.

Specifications

API GL-4

MAN 341 Typ Z4

ZF TE-ML 01L / 02L / 16K

DAF

Eaton Europe (extended drain)

Iveco

Renault

Volvo 97307

ZF TE-ML 08 / 13 / 24A

Typicals

| | |
|--------------------------------------|-------|
| Density at 15 °C, kg/l | 0,858 |
| Viscosity 40 °C, mm ² /s | 59,50 |
| Viscosity 100 °C, mm ² /s | 10,00 |
| Viscosity Index | 155 |
| Flash Point COC, °C | 218 |
| Pour Point, °C | -39 |
| Total Base Number, mgKOH/g | 4,2 |

Available packagings



37507
15 L Bag in
Box



32744
20 L Bag in
Box



57018
20 L pail



35131
20 L can



12175
60 L drum



34553
200 L drum



12271
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.