

Product Information 01.30.60

07-05-2024

Expulsa 10W-40

Description

Expulsa 10W-40 is a semi-synthetic engine oil especially for use in all heavy-duty 4-stroke motorcycles. Its unique formula was designed in partnership with Honda, Suzuki, Kawasaki and Yamaha, in line with the very latest technologies. These leading manufacturers always recommend motor oil specifically developed as a motorcycle oil. A mix of premium synthetic and mineral base oils provides the product with the following features:

- High resistance to wear, corrosion and foaming
- Long replacement intervals
- A very strong lubricating film, even at extremely high operating temperatures
- Minimal ash deposits
- A smooth cold start is possible
- Low oil consumption
- Excellent dispersion and detergency

Application

Expulsa 10W-40 is specially made for use in all 4-stroke motorcycles, including European models, whether or not fitted with a wet clutch. The product is also suitable for motorcycles with the latest catalyst technologies. Special attention has been paid to achieving maximum friction in the clutch, even under very high oil temperatures, so that gear changing is as quiet as possible when the engine's operating temperature has not yet been reached.

Specifications

API SL

JASO MA2

Typicals

Density at 15 °C, kg/l	0,867
Viscosity -25 °C, mPa.s	3200
Viscosity 40 °C, mm ² /s	85,60
Viscosity 100 °C, mm ² /s	14,00
Viscosity Index	168
Flash Point COC, °C	218
Pour Point, °C	-33
Total Base Number, mgKOH/g	7,7
Sulphate Ash, %	0,94

Available packagings



02227
1 L bottle



37548
15 L Bag in
Box



37181
20 L Bag in
Box



12177
60 L drum



12273
208 L drum



33422
1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.