

Product Information 09.30.01

26-04-2024

Kroon-Oil Cleansol

Description

Cleansol is a low-aromatic degreaser, based on a highly refined solvent. Thanks to the selected active-surface substances, an optimally cleaned effect is obtained. Cleansol is non-aggressive and does not pose a fire risk as it has a high flash point.

Application

Cleansol removes oil, grease, dirt and cleans other dirty components of engines, machines, etc. with ease. Its strong cleaning power, low price and limited evaporation make Cleansol highly economical in use. Apply Cleansol to the surface to be cleaned, using a brush or spray. Combining Cleansol with a small parts cleaner is highly recommended. Cleansol must not be released directly into municipal sewers or surface water.

Typicals

Density at 15 °C, kg/l	0,805
Viscosity 20 °C, mm ² /s	2,50
Viscosity 40 °C, mm ² /s	1,98
Viscosity 100 °C, mm ² /s	0,60
Flash Point PM, °C	73
Pour Point, °C	-42

Available packagings



13039
30 L can



13122
60 L drum



13216
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.