

Product Information 07.10.02

25-04-2024

Multi Purpose Grease 3

Description

Multi Purpose Grease 3 is based on highly refined base oils containing lithium soap as a thickening agent. It is supplemented with additives to achieve the following properties:

- Strong adhesion to metal
- Outstanding water displacement
- Excellent stability
- Effective resistance to corrosion and wear
- Excellent pumpability

Application

Multi Purpose Grease 3 is used for the lubrication of ball bearings and wheel hubs and is also suitable for the lubrication of universal joints and chassis pivots in vehicles.

Specifications

N.L.G.I. Klasse 3

DIN 51 502, K 3 K-20

Typicals

Penetration (worked), 0,1 mm	235
Dropping Point, °C	190
Temperature Limits, °C	-25/120
Base oil Viscosity, 40 °C, mm ² /s	110,00

Available packagings



34070
600 g pot



38025
18 kg pail



13102
50 kg drum



13220
180 kg drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.