

## Product Information 07.10.13

25-04-2024

### Labora Grease

#### Description

Labora Grease is a premium, soap-based grease, formulated using the latest generation of lithium-complex soap and is supplemented with special anti-corrosion, anti-wear and 'Extreme Pressure' additives to achieve the following properties:

- Very strong adhesion to metal
- Excellent stability, as a result of which a long service life can be achieved
- Effective resistance to corrosion and wear
- Excellent pumpability
- Outstanding 'Extreme Pressure' properties
- Resistant to shock, vibrating and sudden loads
- Unleaded and nitrite-free; contains non-toxic ingredients
- Can be mixed with mineral oil-based lithium greases

#### Application

Labora Grease is a premium, multipurpose grease that is able to withstand extremely heavy-duty applications in a range of different industrial sectors. Some examples are:

- Heavy-duty bearings of both sliding and ball bearings, slow and fast rotating
- Lubrication that is subjected to high temperatures in which peak temperatures of 225 °C may occur
- When a very long service-life is required
- Heavy-duty, slow-running bearings in earth moving, agriculture and industry

#### Specifications

N.L.G.I. Klasse 2-3

DIN 51 502, KP 2-3 P-30

#### Typicals

Penetration (worked), 0,1 mm	260
Dropping Point, °C	260
Temperature Limits, °C	-30/150
Base oil Viscosity, 40 °C, mm <sup>2</sup> /s	210,00

#### Available packagings



13401

400 g cartridge



38033

18 kg pail



13121

50 kg drum



13218

180 kg drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.