

Product Information 10.10.01

26-04-2024

Kroon-Oil Antifreeze

Description

Antifreeze is a modern antifreeze, based on monoethylene glycol, supplemented with additives to achieve the following properties:

- Outstanding protection of all metals that are used in modern engines and cooling systems
- Does not affect gaskets and hoses
- Very effective resistance to foam formation
- Outstanding protection of aluminium cylinder heads

Application

Antifreeze can be used throughout the year in the cooling systems of petrol and diesel engines. This antifreeze should be further diluted with demineralised water to the recommended ratio before use.

Specifications

BS 6580:2010

Typicals

| | |
|-----------------------------------|-------|
| Density at 15 °C, kg/l | 1,129 |
| pH - 33% in water | 8,0 |
| Reserve alkalinity, pH | 21,0 |
| Watercontents, % | 3,50 |
| Watercontents, % | <5,5 |
| Crystallizationpoint: 30 vol%, °C | -18 |
| Crystallizationpoint: 35 vol%, °C | -22 |
| Crystallizationpoint: 40 vol%, °C | -26 |
| Crystallizationpoint: 45 vol%, °C | -31 |
| Crystallizationpoint: 50 vol%, °C | -38 |

Available packagings



04202
1 L bottle



04301
5 L can



14006
20 L can



14104
60 L drum



14204
208 L drum



14218
1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.