

Product Information 06.30.20

15-07-2024

Kroon-Oil LHM +

Description

LHM+ is a special hydraulic oil, based on special base oils, supplemented with additives to achieve the following properties:

- An extremely high and stable viscosity index
- A very low pour point
- Does not affect oil-proof seals:
- High resistance to foaming

Application

LHM+ is suitable for hydropneumatic suspension systems in Citroën and all other automotive applications for which an LHM fluid is recommended. LHM+ complies with the latest special Citroën requirements.

Specifications

PSA B71 2710

ISO 7308

Typicals

Density at 15 °C, kg/l	0,837
Viscosity -40 °C, mm ² /s	1150
Viscosity 40 °C, mm ² /s	18,60
Viscosity 100 °C, mm ² /s	6,20
Viscosity Index	330
Flash Point COC, °C	125
Pour Point, °C	-50
Acid number, mgKOH/g	0,05
Boiling Point (reflux) , °C	291
Analinepoint, °C	95

Available packagings



04208
1 L bottle



39038
20 L pail



14106
60 L drum



14216
208 L drum



35189
1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.