

## Product Information 01.10.43

17-05-2025

### Multifleet Gas Engine LA 40

#### Description

Multifleet Gas Engine LA 40 is a gas engine oil. It is suitable for the lubrication of 4-stroke gas engines, in which gases of a lower sulphur content are used. The use of high quality base oils combined with special additives results in the following properties:

- Reduction of deposits in the combustion chamber and on the valves
- Good noise reducing properties
- Good oxidation resistance
- Strong acid neutralisation capacity
- Excellent cleaning properties
- Good protection against wear
- Excellent filterability

#### Application

Multifleet Gas Engine LA 40 is suitable for 4-stroke gas engines that require lower acid neutralization capacity. This product can be applied when natural gas, biomass gas or sewage gas are used. Application of this motor oil contributes to a longer service life and decreased maintenance costs, because longer service intervals are possible. Its lower phosphate content means that the service life of the catalytic converter can be extended.

#### Typicals

Density at 15 °C, kg/l	0,894
Viscosity 40 °C, mm <sup>2</sup> /s	143,00
Viscosity 100 °C, mm <sup>2</sup> /s	14,70
Viscosity Index	102
Flash Point COC, °C	254
Pour Point, °C	-21
Total Base Number, mgKOH/g	5,1
Acid number, mgKOH/g	1,84
Sulphate Ash, %	0,45

#### Available packagings



32658  
20 L pail



37890  
20 L can



32659  
60 L drum



35715  
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.