

Product Information 09.50.02

05-05-2024

Kroon-Oil Kroontex SDC

Description

Kroontex SDC is a preservation fluid suitable for the long-term preservation of machines and machine components. The product consists of vaseline-type ingredients, supplemented with a mineral solvent, special water dispersant and corrosion resistant additives to achieve the following properties:

- Good water dispersant qualities: damp parts need not be dried first
- Easy to remove with a mineral solvent
- A good demulsifier: the fluid can be separated effectively from water
- Good surface coat of approx. 10 µm: is able to recover if subjected to light damage
- Good resistance to corrosion: minimum duration of protection is ± 24 months for internal storage and ± 12 months for outdoor storage without a cover

Application

Kroontex SDC is a preservative fluid for the industrial sector, suitable for the long-term preservation of machines and machine components. It can be applied by dipping or spraying, or with a soft brush. Kroontex SDC can be removed with a degreaser (mineral or alkaline) and/or a pressure washer.

Typicals

Density at 15 °C, kg/l	0,828
Viscosity 20 °C, mm ² /s	48,00
Flash Point PM, °C	65

Available packagings



14040
30 L can



14211
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.