

Product Information 06.20.1019-04-2024

Scoogear 75W-90

Description

Scoogear 75W-90 is an extremely modern, synthetic transmission oil specially developed for scooters. By using low-viscosity, synthetic base oils combined with advanced additives, the following properties are achieved:

- Good 'Extreme Pressure' properties provide extra protection against wear
- Excellent resistance to high operating temperatures, which ensures a longer service life of the oil
- $^{\bullet}\,$ Ensures outstanding gear-changing, even at extremely high or low temperatures
- Prevents foaming

Application

Scoogear 75W-90 has been specially developed for optimal use in most heavy-duty transmissions in the current generation of scooters.

Specifications

API GL-5

Typicals

| Density at 15 °C, kg/l | 0,872 |
|--------------------------------------|-------|
| Viscosity 40 °C, mm ² /s | 80,90 |
| Viscosity 100 °C, mm ² /s | 14,80 |
| Viscosity Index | 192 |
| Flash Point COC, °C | 190 |
| Pour Point, °C | -45 |

Available packagings



22016 100 ml bottle

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.