

Product Information 09.50.06 25-04-2024

SMO 1830

Description

SMO 1830 is a mineral oil that is mainly consists of a mixture of saturated paraffin and cycloparaffin hydrocarbons. As a result of intensive refining, this oil is acid-free and almost colour and odour-free. Thanks to the high level of purity, the product can be used for many different purposes. With a useful turn-and-dose cap for clean and controlled application. Turn the cap one quarter turn and squeeze a drop from the bottle.

Application

SMO 1830 has a very high level of purity and is free of acid. These properties mean that the product can be used for:

- Lubricating precision engineering equipment
- Sewing machines and other textile-related machinery Please note! SMO 1830 should not be used in the medical and food industries, in which food products may come into contact with the oil.

Typicals

Density at 15 °C, kg/l	0,858
Viscosity 20 °C, mm ² /s	54,00
Viscosity 40 °C, mm²/s	22,00
Viscosity 100 °C, mm ² /s	4,40
Viscosity Index	109
Flash Point PM, °C	101
Flash Point COC, °C	170
Pour Point, °C	-9

Available packagings













22017 100 ml bottle 1 L bottle

33644 20 L pail

60 L drum

208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.