Product Information 01.20.68

17-04-2024

Dieselfleet Super G 15W-50

Description

Dieselfleet Super G 15W-50 is a modern, universal motor oil. Dieselfleet Super G 15W-50 is manufactured using high-grade solvent refined base oils, supplemented with balanced additives. This multigrade motor oil has the following properties:

- Excellent detergency prevents deposits forming in the engine
- Very good dispersion prevents the formation of sediment and sludge
- Very resistant to corrosion and foaming
- A high and stable viscosity index
- A low sulphate ash content
- High wear resistance, resulting in reduced wear of piston rings and cylinder wall

Application

Dieselfleet Super G 15W-50 is a universal motor oil that is suitable for lubricating both petrol and diesel engines with or without a turbocharger. It can be used under high-impact operating conditions in any season. This oil is ideally suited for mixed vehicle fleets and can be used in Euro 3 and Euro 4 engines, among others. The special composition enables longer oil change intervals when using this motor oil.

Specifications

ACEA A3/B4, E7
API CI-4/SL
DTFR 15B110

Typicals

Density at 15 °C, kg/l	0,867
Viscosity -20 °C, mPa.s	6000
Viscosity 40 °C, mm²/s	134,00
Viscosity 100 °C, mm²/s	17,50
Viscosity Index	144
Flash Point COC, °C	215
Pour Point, °C	-33
Total Base Number, mgKOH/g	11,1
Sulphate Ash, %	1,45

Available packagings

35737
200 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com